



[PEWT-4000] PITBULL™ WATER FIRE TANKERS

FIRE CONTROL AND PROTECTION UNITS BUILT TO YOUR REQUIREMENTS.

Our agricultural low speed trailer is fitted with an 8-ton axle, reinforced chassis and tank combination,
and a universal tractor tow hitch.

The 4000-litre tank is fabricated with Corten-steel and internally coated for rust prevention. Fitted with modern firefighting equipment, and latest design hydraulic technology, your fire risk is underwritten by a proven product.

BUILT TOUGH. ENGINEERED TO LAST.

TECHNICAL DATA : SPECIFICATIONS SHEET

Tyre size	1100.R20
Litres per minute:	400 – 450 L/p.m.
Water pump:	1" Twin wide
Water pump:	Hydraulically driven.
Heavy duty hose reels:	Galvanized (x 2)
Water cannon fitted:	360 Degrees.
Corten steel tank:	4 000L
Non-Toxic lining:	2 Coats
Axle:	8-Ton
Brakes:	Hydraulic
Hitch:	Certified BUGLE agricultural



Custom tank to chassis design
Fitted with gold-line hose (25mm x 60 meter) and couplers.
All-round sprayers installed in hand railing with 360-degree cooling jets
Custom built storage and tool boxes
Plated deck - non-slip
Primer tank
Tractor drawn
Firefighting equipment storage and toolboxes (lockable).
Main tank level gauge.
Self-filling system.
Rear water expulsion for dust control.

12 Month Warranty on all structural and hydraulic components.*

QUALITY | PRECISION | PERFORMANCE

